

Declaration of Performance (DoP)

No.: 13/2017

Release date: 11th August 2026

Revision No.: 1

Name of product: **Plywood sheets ABSORPTION – with anti-noise rubber**

Product intended for: for external use as non-structural components

Producer: **DYAS.EU, a.s.**
Dukelských hrdinů 3653/1
695 58 Hodonín, Czech Republic

Company registration Nr.: 271 176 51

Plant: Veselská 384, 687 24 Uherský Ostroh, Czech Republic

Assessment method: 3

Harmonized standard: EN 13986+A1

Additional information to the product:

The formaldehyde emission test is tested in accordance with EN 717-1 at an accredited laboratory. The measured formaldehyde emission complies with the requirements of COMMISSION REGULATION (EU) 2023/1464, and the measured formaldehyde emission value is less than 0.062 mg/m³.
Carried out airborne sound insulation measuring according to ČSN EN ISO 10140-2 on 5.4.2012
Issued a test record No.: 91/12 set the sound insulation values in the frequency range 50 - 5000 Hz. **Weighted Sound Reduction R_w (C; C_{tr}) = 31 (-1; -2) dB**

DYAS.EU, a.s., Dukelských hrdinů 3653/1, 695 58 Hodonín,
Provozovna: Veselská 384, 687 24 Uherský Ostroh
IČO: 27117651, DIČ: CZ27117651, Fax: + 420 572 591 439, dyas@dyas.eu
Společnost je zapsaná v OR KS v Brně, oddíl B, vložka 4486, www.dyas.eu

Kvalita ve všech vrstvách - založeno 1930

www.dyas.eu



Product features:

No.	Basic characteristics	Feature	Harmonized norm
1	Bending strength – longwise (minimal guaranteed strength)	60,00 N / mm ²	EN 310
	Bending strength – crosswise (minimal guaranteed strength)	30,00 N / mm ²	EN 310
2	Gluing quality – EN 636 - 3	Gluing class – 3	EN 314 - 2
5	Formaldehyde release	≤ 0,062 mg/m ³	EN 717-1
6	Reaction to fire without air gap behind a wood-based board (thickness ≥ 9mm)	D-s2,d0 for floors Dfl – s1	The tabulated value specified in EN 13986+A1
	Reaction to fire with closed or open air gap up to 22 mm (thickness ≥ 9 mm)	D-s2, d2	
	Reaction to fire with closed air gap behind the wood-based board (thickness ≥ 15mm)	D-s2,d0 for floors Dfl – s1	
	Reaction to fire with open air gap behind the wood-based board (thickness ≥ 18mm)	D-s2,d0 for floors Dfl – s1	
7	Water vapour permeability – diffusion resistance factor μ humid	90	EN 13986+A1
	Water vapour permeability – diffusion resistance factor μ dry	220	EN 13986+A1
8	Sound-transmission loss – applies to the frequency range from 1 kHz to 3 kHz (thickness 10 – 50mm)	31 dB	ČSN EN ISO 10140-2
9	Thermal conductivity - λ	0,17 W/(m.K)	EN 13986+A1
10	Biological durability – class of danger	3	EN 335
11	Pentachlorophenol content- no substance containing pentachlorophenol was used in the manufacture	not determined	EN 13986+A1
12	Air permeability	not determined	EN 12114

Product features – Plywood sheets ABSORPTION – with anti-noise rubber are in compliance with the properties in the table “Product features”.

This declaration of performance is issued under the responsibility of DYAS.EU, a.s.

Signed on behalf of the producer and his name:

.....
Radek Nejeschleba
Managing Director

DYAS
DYAS.EU, a.s.
Dukelských hrdinů 3653/1, 695 58 Hodonín
Plant: Veselská 384, 687 24 Uherský Ostroh

In Uherský Ostroh 11th August 2026

2/2

DYAS.EU, a.s., Dukelských hrdinů 3653/1, 695 58 Hodonín,
Provozovna: Veselská 384, 687 24 Uherský Ostroh
IČO: 27117651, DIČ: CZ27117651, Fax: + 420 572 591 439, dyas@dyas.eu
Společnost je zapsaná v OR KS v Brně, oddíl B, vložka 4486, www.dyas.eu



Kvalita ve všech vrstvách - založeno 1930

www.dyas.eu